

EQUIPMENT PRODUCT INFORMATION

TD200 AUTODRY TUNNEL

SMART DRYING, SEAMLESS INTEGRATION, MAXIMUM EFFICIENCY

DESCRIPTION

Engineered for high-volume meat and cheese processors, the TD200 AutoDry tunnel delivers unmatched drying performance with intelligent automation, hygienic design, and minimal downtime so your line runs cleaner, faster, and more reliably. Remote monitoring and full-line automation available when paired with the latest CRYOVAC[®] vacuum rotary systems, streamlining operations and maximizing efficiency from a single control point. As a trusted partner to every major food processor, CRYOVAC[®] delivers unmatched reliability, scale, and expertise in food packaging solutions.



KEY BENEFITS

OPERATIONAL EFFICIENCY

- Keep production running efficiently with superior drying performance and 99% uptime
- Up to 30% energy savings compared to legacy models with proprietary variable speed control and intelligent blower technology
- Monitor real-time equipment performance through SEE Smart Link to help boost efficiency, catch issues early, and reduce downtime with faster troubleshooting
- Eliminate bottlenecks, maintain consistent product flow and streamline upstream and downstream processes with integrated equipment

PRODUCT INTEGRITY

- Unmatched drying performance reduces residual moisture, helping prevent microbial growth and packaging defects that can compromise product quality and shelf life
- Improves packoff operations by reducing residual moisture, helping prevent damage to cardboard shipping boxes and ensures cleaner, more reliable case packaging

BRAND EXPERIENCE

- Superior drying performance ensures packages are clean and visually appealing, reinforcing a premium brand image in retail environments
- Intelligent automation and hygienic design help maintain consistent product presentation and safety, building consumer trust in quality

TECHNICAL DATA

MACHINE DIMENSIONS

Max Length	62.99" (1600 mm)
Width	45.28" (1150 mm)
Height	70.9" (1800 mm)

WEIGHT

Weight	1700 lbs (771 kg)
--------	-------------------

OPERATORS

Required	1 to monitor only
----------	-------------------

PRODUCT DIMENSIONS

Length	Up to 56" (1422 mm)
Width	22" (555 mm)
Height	9" (225 mm)
Weight	220 lbs (100 kg) max

SPEED

Working Speed	Variable speed up to 75 FPM
---------------	-----------------------------

UTILITIES

Air	Pressure 0.6 - 1.0 MPa (90 - 140 psi) Consumption 0.05 Nm ³ /h Connection G 3/8" Internal Thread
Electrical	460 VAC, 60 Hz, 3 Phase + PE, 60 Amp 75 kVA Isolation Transformer Recommended

LINE LAYOUT EXAMPLE

