

## EQUIPMENT PRODUCT INFORMATION

### AUTOVAC 95

## HIGH-SPEED ROTARY VACUUM CHAMBER MACHINE FOR SPECIALTY CUTS



## DESCRIPTION

The CRYOVAC<sup>®</sup> brand AutoVac 95 Vacuum Chamber System delivers reliable, high-quality vacuum packaging for processors handling a wide range of products from fresh meat and poultry to processed meats and cheese. Designed for flexibility, the single-chamber system easily accommodates varying product shapes and sizes, while the integrated buffer conveyor supports smooth, consistent feeding in a compact footprint. The AutoVac 95 is the perfect fit for mid-sized operations looking to balance performance, product quality, and space efficiency.

## KEY BENEFITS

### OPERATIONAL EFFICIENCY

- Keep production moving with consistent, dependable cycle times that support daily throughput needs
- Simplify operation and changeovers with an intuitive touchscreen interface and programmable settings
- Handle a wide mix of products with a spacious vacuum chamber designed for flexibility
- Maintain hygienic standards with a washdown-capable design that supports efficient cleaning

### PRODUCT INTEGRITY

- Preserve freshness, flavor, and shelf life by removing oxygen and minimizing purge
- Protect product integrity using CRYOVAC<sup>®</sup> brand oxygen barrier bags with proven sealant performance

### BRAND EXPERIENCE

- Deliver consistent, professional packages that elevate shelf appeal
- Highlight product quality with high-gloss, transparent packaging materials
- Support strong branding and differentiation with compatibility for two-sided printed graphics

# TECHNICAL DATA

## MACHINE DIMENSIONS

Max Length	170" (4305 mm)
Width	50" (1260 mm)
Height	75" (1890 mm)
Seal Bars	L/W - 59"/1.2" (1500 mm/30 mm) 1.2"/2.5" (30 mm/65 mm) Distance Between 30" (765 mm)

## WEIGHT

Weight	7000 lbs (3200 kg) approx.
--------	----------------------------

## OPERATORS

Required	1
----------	---

## PRODUCT DIMENSIONS

Length	8.6" (225 mm)
Height	29.3" (745 mm)

## BAG DETAILS

Width	Up to 59"
Length	Up to 29"
Bag Types	Current range of CRYOVAC® brand shrink bags (automated feeding only with OSB™ bags)

## SPEED

Working Speed	3-3.3 cycles per minute with belt at maximum level
---------------	--

*Speed is dependent on product type and pumps used*

## UTILITIES

Air	0.6 MPa
Electrical	4000 V (other voltages available upon request); No. Phases 3 + earth; 50/60 Hz
Energy Consumption	1 kWh without vacuum booster pump per hour 4.2 kWh with vacuum booster pump per hour 15 Nm <sup>3</sup> /h

## LINE LAYOUT EXAMPLE

